

## PRODUCT INFORMATION

### G-ARC QS QUICK SET GROUT

**G-ARC QS Grout** is a 100% solids epoxy grouting system that cures to a strong high performance grout, exhibiting excellent mechanical strength and strong adhesion. G-ARC QS grout has good flow ability plus good resistance to chemicals. With fast curing and low exotherm, G-ARC QS has excellent bond strength up to 15Mpa when applied to abrasive blasted steel. G-ARC QS can be utilised in a variety of applications such as a base or machine grout, adhesive, chemical anchor grout, void filler, floor repairs and the such. Mixing with a suitable quartz aggregate forms an economical epoxy grouting system

**Surface Preparation:** The correct procedures are essential to give a high level of adhesion.

Removal of all oils and grease contamination using approved cleaning methods prior to abrasive blasting.

Abrasive blast to give a profile of 75 to 100 microns and a near white metal finish.

Smaller areas may be prepared with hand tools to clean and abrade surface.

**Mixing Product:** Material temperature should be between 15 and 30 °C for mixing.

Empty both pails A and B and mix until uniform in colour.

Use a mechanical mixer or manually stir.

Mixed material can be poured into the application.

**Application:** Apply mixed product by either pouring or spatula application.

#### FEATURES

*High mechanical strength*

*Quick Setting*

*Pourable system*

*Easy to apply*

*High strength adhesion*

#### PROFILE

*Colour* Grey

*Pot life @25°C* 10  
*min*

*Cure Time @25°C* 1 hour

*Kit Size* 1.2kg

